

ECC-54K5

Indoor Operation, Digital signal processing, high quality picture
2.5" plastic HAICH dome camera, Sony 1/3" Super HAD CCD
Horizontal Resolution of 540TVL, Automatic White Balance (AWB)
True Day&Night IR filter, Auto Electronic Shutter & Auto Gain Control
IR power-on, Color to B/W automatically at night, 23 Leds
valid distance: 15-30M, Lens 3.6mm, 12VDC 400mA, CE, FCC, RoHS Compliance



Analog IR Color Camera

Range of Application:

Home, community, villa, office, laboratory, classified papers office, information center, factory storehouse, financial system of the bank, store of valuables, star-rated hotel, Traffic road and other places require safety.

ECC-54K5

Image Sensor	1/3" Sony Super HAD CCD
Pixels	PAL:795(H)x596(V) NTSC:811(H)x508(V)
Resolution	540TV Lines
Minimum Illumination	0.01 LUX
Gamma	0.45/1 (Set To 0.45 Before shipment)
S/N Ratio	More than 48dB
Sync system	Internal Sync.
Scanning system	2:1 Interlace
Electronic Shutter	NTSC:1/60-1/100,000 second PAL:1/50-1/100,000 Second
Lens	3.6mm
Video Output	1.0Vp-p,75Ω, Composite
Audio Output	N/A
Auto Iris Control	N/A
AGC	Auto
BLC	Auto
AWB	Auto
Exposure Mode	N/A
Operation Housing	2.5"plastic HAICH dome camera
Installation Optional	N/A
IR distance	15-30M
IR Transmission Wave	850nm
IR Transmission Angle	30°, 45°, 60°
Bulb Dimeter	Φ 5mm
Number of IR	23 IR LEDs
Standard Size	Φ94×65(H)mm
Operating Temp	-10°C~+50°C
Humidity	<90%RH
Power Supply	DC12V
Power Consumption	400mA

