

ECC-54C3

Indoor Operation, Digital signal processing,high quality picture
3.5" Dome plastic triangle camera, Ultra-transparent Acrylics housing
Sony 1/3" Super HAD CCD, Horizontal Resolution of 540TVL
Automatic White Balance (AWB), True Day&Night IR filter
Auto Electronic Shutter & Auto Gain Control, Audio function
Lens 3.6mm, 12VDC 150mA, CE, FCC, RoHS Compliance



Analog Color Camera

Range of Application:

Home, community, villa, office, laboratory, classified papers office, information center, factory storehouse, financial system of the bank, store of valuables, star-rated hotel, Traffic road and other places require safety.

ECC-54C3

Image Sensor	1/3" Sony Super HAD CCD
Pixels	PAL:795(H)x596(V) NTSC:811(H)x508(V)
Resolution	540TV Lines
Minimum Illumination	0.01 LUX
Gamma	0.45/1 (Set To 0.45 Before shipment)
S/N Ratio	More than 48dB
Sync system	Internal Sync.
Scanning system	2:1 Interlace
Electronic Shutter	NTSC:1/60-1/100,000 second PAL:1/50-1/100,000 Second
Lens	3.6mm fixed iris lens (2.8 / 4.3 / 6.0 / 8.0 / 12 /16mm for option)
Video Output	1.0Vp-p,75Ω, Composite
Audio Output	2.0Vp-p RCA
Auto Iris Control	N/A
AGC	Auto
BLC	Auto
AWB	Auto
Exposure Mode	N/A
Operation Housing	3.5" Dome Plastic Triangle Camera Housing
Installation Optional	N/A
IR distance	N/A
IR Transmission Wave	N/A
IR Transmission Angle	N/A
Bulb Dimeter	N/A
Number of IR	N/A
Standard Size	Φ100×70(H)mm
Operating Temp	-10°C~+50°C
Humidity	<90%RH
Power Supply	DC12V
Power Consumption	150mA

